



APX™ 6000 SINGLE-BAND PORTABLE RADIO



From day one, the single-band APX 6000 P25 portable radio has delivered legendary APX ruggedness and reliability, without compromising on the form factor or features required for routine activities and extreme emergencies. Now, as the ever-increasing needs of public safety personnel grow, we are evolving the APX 6000 to support newer technologies like Wi-Fi®, Adaptive Audio Engine and Bluetooth® 4.0 wireless technology. These advances help improve the operational efficiency and response time of public safety agencies while enhancing the safety of personnel and communities.

VOICE AND DATA, ALL AT ONCE

Update your radio fleet without interrupting voice communications with secure Wi-Fi. This dramatically improves the speed of configuring new codeplugs, firmware and software features over-the-air via Radio Management*. Agencies can pre-provision up to 20 secure Wi-Fi hotspots so personnel can easily access updates at the facility or in the field.

HEAR AND BE HEARD

The APX 6000 is equipped with a 3-watt speaker, 3 integrated microphones and the Adaptive Audio Engine. This changes the level of noise suppression, microphone gain, windporting and speaker equalisation to produce clear and loud audio in any environment.

SEAMLESS ON-SCENE COMMUNICATION

Ensure fast and seamless communication and collaboration across all responders arriving on a scene. Mission Critical Geofence automatically changes a radio's active talkgroup based on its GPS location and an agency-defined virtual barrier. For example, an incident commander can create a geofence around the 3-block radius of a burning building so that all arriving personnel are automatically placed in the same talkgroup.

EMERGENCY FIND ME

Bluetooth 4.0 places a wide range of wireless accessories at your disposal and provides personnel with an added level of security by improving response time in emergencies. With Emergency Find Me, a Bluetooth-enabled beacon signal guides other Bluetooth-enabled APX radios within range to assist the user in distress.



*Radio Management application simplifies APX radio configuration and management by programming up to 16 radios at one time and tracking which radios have been successfully programmed, providing a clear view of the entire radio fleet and a codeplug history for each radio.

PRODUCT DATA SHEET

APX 6000 SINGLE-BAND PORTABLE RADIO



SPECIFICATIONS

RF BANDS

- 700/800 MHz, VHF, UHF Range 1 & UHF Range 2
- 9600 Baud Digital APCO P25 Phase 1 FDMA and Phase 2 TDMA Trunking
- 3600 Baud SmartNet®, SmartZone®, SmartZone, Omnilink Trunking
- Digital APCO 25, Conventional, Analogue MDC 1200, Quick Call II System Configurations Narrow and Wide Bandwidth Digital Receiver (6.25 kHz Equivalent/25/20/12.5 kHz)¹

STANDARD FEATURES

- Mission Critical Wireless Bluetooth® 4.0 (LE)²
- Emergency Find Me²
- ASTRO® 25 Integrated Voice & Data
- Integrated GPS/GLONASS for Outdoor Location Tracking
- Voice Announcements
- ISSI 8000 Roaming
- Radio Profiles
- Dynamic Zone
- Intelligent Lighting
- Single-Key ADP Encryption
- IP68 submersion (2 metres, 2 hours)
- IMPRES 2 Battery (PMNN4485)
- Text Message

PROGRAMMING

- Utilises Windows Customer Programming Software (CPS) with Radio Management

ADAPTIVE AUDIO ENGINE (OPTIONAL)

- 3-W Speaker with Adaptive Equalisation
- Adaptive Dual-Sided Operation
- Adaptive Noise Suppression Intensity
- Adaptive Gain Control
- Adaptive Windporting

OPTIONAL FEATURES

- Wi-Fi 802.11 b/g/n
- LEX L10 Collaboration
- RFID Volume Knob
- Multi-key for 128 keys and Multi-Algorithm
- Programming Over Project 25 (OTAP)
- Over the Air Rekey (OTAR)
- Digital Tone Signaling
- Mission Critical Geofence
- P25 Authentication
- Man Down Capability
- High Impact Green and Public Safety Yellow Coloured Housing Options
- Rugged Option: IP68 (2m/4hr), Mil Std 512.X Delta - T
- Listed by UL to the standards ANSI/TIA 4950-A and CAN/CSA C22.2 NO. 157-92 Classification Rating: Class I, Division 1, Groups C, D; Class II, Division 1, Group E, F, G; Class III, Hazardous (Classified) Locations. ANSI/ISA 12.12.01-2015 and CAN/CSA C22.2 No. 213-15; Class I, Division 2, Groups A, B, C, D; T3C. Tamb = -25° C to +60° C. when used with Motorola Solutions Battery: NNTN8921A NNTN8930A 7.4V

¹ Per the FCC Narrowbanding rules, new products (APX6000 UHF1, UHF2) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25 KHz for United States - State & Local Markets only.

² Compatible with BT 2.1, HSP, PAN, DUN and SPP Profiles found in off-the-shelf Bluetooth accessories and Bluetooth 4.x

TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS

		700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz	763-776, 793-806 MHz	136-174 MHz	380-470 MHz	450-520 MHz
	800 MHz	806-824, 851-870 MHz			
Channel Spacing		25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj ¹		1-3 Watts Max	1-6 Watts Max	1-5 Watts Max	1-5 Watts
Frequency Stability ¹ (-30°C to +60°C; +25°C Ref.)		±0.00010 %	±0.00010 %	±0.00010 %	±0.00010 %
Modulation Limiting ¹		±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz	±5 kHz / ±4 kHz / ±2.5 kHz
Emissions (Conducted and Radiated) ¹		-75 dB	-75 dB	-75 dB	-75 dB
Audio Response ¹		+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	25k	-52 dB	-55 dB	-52 dB	-52 dB
	25.5k	-47 dB	-50 dB	-47 dB	-46 dB
Audio Distortion ¹	700 MHz 800 MHz	1.00 %	1.00 %	1.00 %	1.00 %

PRODUCT DATA SHEET
APX 6000 SINGLE-BAND PORTABLE RADIO

BATTERIES FOR APX 6000				
Battery Capacity / Type	Dimensions (HxWxD)	Weight	Battery Part Number	Battery Capacity
Li-Ion IMPRES 2 2550mAh ¹	3.4" x 2.3" x 1.5"	5.0 oz	PMNN4485	2550 mAh
Li-Ion IMPRES 2 3400mAh	3.4" x 2.3" x 1.7"	6.5 oz	PMNN4486	3400 mAh
Li-Ion IMPRES 2 4850mAh	5" x 2.3" x 1.7"	11.0 oz	PMNN4487	4850 mAh
Li-Ion IMPRES 2 5100mAh	5" x 2.3" x 1.7"	11.0 oz	PMNN4494	5100 mAh
Li-Ion IMPRES 2 2650 mAh ²	3.4" x 2.3" x 1.7"	5.7 oz	NNTN8930	2650 mAh
Li-Ion IMPRES 2 4500mAh ²	5" x 2.3" x 1.7"	11.0 oz	NNTN8921	4500 mAh

¹ The standard shipping battery for the APX6000

² HAZLOC approved.

RADIO MODELS

	MODEL 1.5	MODEL 2.5	MODEL 3.5
Display	Full bitmap monochromatic LCD top display 1 line text x 8 characters 1 line of icons No menu support Multi-colour backlight	Top display plus: Full bitmap colour LCD display 4 lines of text x 14 characters 2 lines of icons 1 menu line x 3 menus White backlight	Top display plus: Full bitmap colour LCD display 4 lines of text x 14 characters 2 lines of icons 1 menu line x 3 menus White backlight
Keypad	none	Backlit keypad 3 soft keys 4 direction Navigation key Home and Data buttons	Backlit keypad 3 soft keys 4 direction Navigation key 4x3 keypad Home and Data buttons
Channel Capacity ¹	96	1000	1000
FLASHport Memory	64 MB	64 MB	64 MB
700/800 MHz (763-870 MHz)	H98UCD9PW5BN	H98UCF9PW6BN	H98UCH9PW7BN
VHF (136-174 MHz)	H98KGD9PW5BN	H98KGF9PW6BN	H98KGH9PW7BN
UHF Range 1 (380-470 MHz)	H98QDD9PW5BN	H98QDF9PW6BN	H98QDH9PW7BN
UHF Range 2 (450-520 MHz)	H98SDD9PW5BN	H98SDF9PW6BN	H98SDH9PW7BN

Buttons & Switches

Large PTT button ■ Angled On/Off volume control ■ Orange emergency button ■ 16 position top-mounted rotary switch
■ 2-position concentric switch ■ Multi-colour backlight ■ 3-position toggle switch ■ 3 programmable side buttons

Regulatory Information	
	FCC ID
700/800 (764-869 MHz)	AZ489FT7086
VHF (136-174 MHz)	AZ489FT7087
UHF Range 1 (380-470 MHz)	AZ489FT7077
UHF Range 2 (420-520 MHz)	AZ489FT7085

FCC Emissions Designators	
FCC Emissions Designators	11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E ²

Power Supply	
Power Supply	One rechargeable Li-Ion IMPRES 2 2550mAh battery standard (PMNN4485), with alternate battery options available.

¹ Enhancement package available

² Per the FCC Narrowbanding rules, new products (APX6000 UHFRI1, UHFRI2) submitted for FCC certification after January 1, 2011 are restricted from being granted certification at 25 kHz for United States - State & Local Markets only.

RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS					
		700/800	VHF	UHF Range 1	UHF Range 2
Frequency Range/Bandsplits	700 MHz 800 MHz	763-776 MHz 851-870 MHz	136-174 MHz	380-470 MHz	450-520 MHz
Channel Spacing		25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz	25/20/12.5 kHz
Maximum Frequency Separation		Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated ¹		500 mW	500 mW	500 mW	500 mW
Analogue Sensitivity ²	12 dB SINAD	0.25 µV	0.17 µV	0.224 µV	0.203 µV
Digital Sensitivity ³	1% BER (800 MHz)	0.375 µV	0.243 µV	0.298 µV	0.296 µV
	5% BER	0.24 µV	0.15 µV	0.200 µV	0.204 µV
Selectivity ¹	25 kHz channel	-76 dB	-78 dB	-77 dB	-76 dB
	12.5 kHz channel	-70 dB	-73 dB	-67 dB	-67 dB
Intermodulation		-80.1 dB	-80.2 dB	-80.3 dB	-80.2 dB
Spurious Rejection		-75 dB	-78 dB	-80.5 dB	-80.8 dB
FM Hum and Noise	25 kHz	-54 dB	-54.3 dB	-53.5 dB	-52.5 dB
	12.5 kHz	-79 dB	-50.1 dB	-47.5 dB	-47.3 dB
Audio Distortion at Rated ¹		0.90%	0.90%	0.70%	0.70%

1 Measured in the analogue mode per TIA / EIA 603 under nominal conditions

2 Measured conductively in analogue mode per TIA / EIA 603 under nominal conditions.

3 Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions.



PORTABLE MILITARY STANDARDS 810 C, D, E , F & G										
	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Basic Hot	501.5	I/A1, II/A2
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1C3	503.3	I/A1C3	503.4	I	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Immersion	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24	514.6	I/24
Shock	516.2	I, III, V	516.3	I, V, VI	516.4	I, V, VI	516.5	I, V, VI	516.6	I, V, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV



DIMENSIONS OF THE RADIOS WITHOUT BATTERY		
Length	5.47 in	139 mm
Width Push-To-Talk button	2.39 in	60.7 mm
Depth Push-To-Talk button	1.40 in	35.6 mm
Width Top	2.98 in	75.7 mm
Depth Top	1.58 in	40.1 mm
Depth Bottom of Battery	1.24 in	31.5 mm
Weight of the radios without battery	10.9 oz	309 g

ENCRYPTION	
Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL
Encryption Algorithm Capacity	8
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 64 Common Key Reference (CKR) or 16 Physical Identifier (PID)
Encryption Frame Re-sync Interval	P25 CAI 300 mSec
Encryption Keying	Key Loader
Synchronisation	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

GPS/GPS/GNSS SPECIFICATIONS	
Constellations	GPS & GLONASS
Tracking Sensitivity	-164 dBm
Accuracy ²	<5 metres (95%)
Cold Start	<60 seconds (95%)
Hot Start	<5 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted)

RUGGED SPECIFICATIONS	
Leakage (submersion)	MIL-STD-810 C, D, E, F and G Method 512.X Procedure I, IP68 (2 metres, 4 hours)

HOUSING COLOUR	
	Black (Standard), Public Safety Yellow, and High Impact Green

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature ¹	-30 °C to +60 °C
Storage Temperature ¹	-50 °C to +85 °C
Humidity Per MIL-STD	ESD IEC 801-2 KV
Water and Dust Intrusion	IP68 (2 metres, 4 hours)

1 Temperatures listed are for radio specifications. Battery storage is recommended at 25 °C, ±5 °C to ensure best performance.
2 Measured conductively with >6 satellites visible at a nominal -130 dBm signal strength. Specs provided are 95th percentile values.

EMISSION DESIGNATORS		WIRELESS CONNECTIVITY AND SECURITY	
LMR:	8K10F1D, 8K10F1E, 8K10F1W, 11K0F3E, 16K0F3E, 20K0F1E	Frequency Range/Bandsplits:	
Bluetooth:	852KF1D, 1M17F1D, 1M19F1D, 1M04F1D	Bluetooth:	2402 - 2480 MHz, WLAN (Wi-Fi): 2400 - 2483.5 MHz
WLAN (Wi-Fi):	13M7G1D, 17M0D1D, 18M1D1D	WLAN (Wi-Fi) 802.11 b/g/n supports WPA-2, WPA, WEP security protocols; radio can be pre-provisioned with up to 20 SSIDs¹	
		Mission Critical Wireless Bluetooth 2.1 uses 96 bit encryption for pairing & 128 bit encryption for voice, signaling and data. The radio BT supports up to 6 data connections and 1 audio connection	
		Bluetooth 4.0 Low Energy uses 128-bit AES-CCM encryption	

¹ 2400 - 2483.5 MHz for EMEA region and includes guardband.
Channels 1 – 11 used for FCC/IC region.



For more information, visit www.motorolasolutions.com.au

Motorola Solutions Australia Pty Limited

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylised M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2016 Motorola, Inc. All rights reserved. -2016

